

PowerPoint PP-VIP4-0,63t-1/2"-12BSW

Artikel-Nr:

8600571



Connection only with RUD approved components e.g; VCÖH-4, oval link, PP 0,63t kg or the 4 mm VIP chain.


Hint : The VIP chain connection is fool proof. When assembling the components, pay attention to the correct WLL allocation.

- **Can be combined with most commercial lifting means without additional connecting element.**
- **Lifting points pivots 360°.**
- **Large distance between bolt-on surface and load to avoid damage.**
- **Rotatable at nominal WLL, 90° to the bolt-on direction**Lowest kinking possibility due to cardan joint.
- **Suspension ring with enlarged pivoting area.**
- Clear marking of the minimum WLL for all loading directions.
- Variable thread lengths are available for use of threaded holes and through hole fixtures.
- Non removable special bolt (this reduces the risk of non standard bolts).
- Component according to the test criterias of BG/DGUV "GS-OA-15-04".
- Quick and easy installation with just one bolt connection.
- Hand tightening with appropriate wrench is sufficient for a singular lift.
- Please observe torque instructions when lifting point is permanently installed resp. at constant swivelling operations and tilting/ turning actions.

Other important RUD specific information and specialities to our RUD lifting points can be found in the specific user instruction.

PowerPoint PP-VIP4-0,63t-1/2"-12BSW

Artikel-Nr: 8600571



weight	0.24 kg	0.53 lbs
Nominal WLL	630 kg	1385 lbs
T	41 mm	1-5/8"
A	4 mm	5/32"
D	40 mm	1-9/16"
E	36 mm	1-27/64"
F	18 mm	23/32"
M	1/2"-12BSW mm	1/2"-12BSW